

PA/5000LT™ label printer/applicator



Handheld Interface can be mounted anywhere within 8' of the applicator

The industry's fastest, toughest label printer/applicator!

The PA/5000LT is capable of printing and applying up to 110 labels per minute. With rugged steel and aluminum construction, it's tough enough for three-shift operation in the most demanding conditions. That's why it comes with the industry's first 2-year warranty.



Nose-Down PA/5000LT system labeling traypacks



PA/5000LT equipped with front apply swing arm

features & benefits

- **Choice of Print Engines** from Sato®, Zebra® and Datamax®
- **Choice of Printheads:** 203, 300, 406 or 600 dpi resolution
- **Print/Apply Speed** up to 110 ppm
- **Application Versatility** for top, bottom, adjacent, side, leading and trailing panel applications
- **2-Year Warranty:** the industry's first
- **Menu-Driven Interface** for easy set-up and operation
- **Advanced Diagnostics** for fast, accurate troubleshooting
- **Web Monitoring:** low, out and broken conditions
- **Standard Discrete I/O** to communicate status conditions to external devices
- **Message Storage & Editing** capability for stand-alone use
- **Quick-Change** label/ribbon supply
- **Tested & Approved to Meet:** UL-60950, CSA-C22.2 No. 60950, and CE requirements for safety



Designed to deliver versatile 24/7 performance.

Versatile

With a choice of print engines (Sato®, Zebra® or Datamax®) and applicator modules, the PA/5000LT is designed for maximum application versatility.

Quick-Change Supply

No tools required for label/ribbon changes. Standard 13" OD with optional 15" unwind.

Heavy-Duty T-Base Stand

with locking casters.

High-Speed Cylinder

Dual stroke sensors. Tamp assembly includes label-present and auto-retract sensors, allowing labels to be applied 2" to 16" from the applicator.

Pneumatic Module

Dedicated dial indicators and regulators for controlling individual pneumatic functions.

Handheld Interface

with QWERTY keypad and LCD display for access to menus, diagnostics, job and status information. Diagnostic menu tests every sensor and valve in the system. All settings can be password protected. Jobs can be cleared and test labels printed using the keypad. Interface allows networking with other units.

Web Management

provides smooth operation and extended life.

Maximum Label Size

7.2" x 13"

For more information on all Diagraph products, complete specifications, labeling consumables and service, please visit our website:

www.diagraph.com

 **Diagraph®**
An **TW** Company

1 Missouri Research Park Drive • St. Charles, MO 63304 • Phone: 800-722-1125 • Fax: 636-300-2004
Equipment Sales: 800-722-1125 • Service, Parts & Inks: 800-526-2531 • Labeling Consumables: 800-695-0036

© 2004 Diagraph • Printed in U.S.A. • SWIFT • 7/04 • 5M