



KIP-20 INTERFACE PRINTER

The Kingsley KIP-20 Hot Stamp Wire printers feature quick-change fixture systems that minimize set-up time and maximize printing speed to allow for frequent legend changes on a wide range of wire sizes.

Prints on **command** from virtually any wire processor, cutter, stripper, or terminator

Quick-change type system minimizes set-up time and maximizes printing speed


Full-size 40-character typewheels include alphanumerics and symbols mounting up to 28 typewheels

Prints a large range of wire diameters from .038" to .250" OD

KEY FEATURES

- Prints horizontally and vertically on insulated wire and cable, including Teflon, Tefzel, and Kapton
- Small footprint makes it easy to integrate into existing production lines
- Versatile operation options: choose between foot pedal or remote operation
- Double continuous marking for greater production rates since both leading and trailing end marks are applied at the same time

SPECIFICATIONS



Application	Insulated Wire and Cable Including Teflon, PVC, Tefzel, Kapton, etc. (Sizes .038" to .250" OD)
Operation	Pneumatic/Electric, Remote Signal Operation in Conjunction with In-Line Wire Processor. (Also Available as Bench-Top Operation with Foot Pedal)
Printing Method	Hot Stamp Process; Full-Size, 40 Characters per Typewheel (Maximum 28 Typewheels)
Printing Area	1 Line x 2.9" (73.6mm) on Sizes .038" (.96mm) to .250" (6.3mm) O.D. (Note: Wire Sizes Over .250" (6.3mm) O.D. Require Special Fixtures)
Printing Characteristics	One-Line, Horizontal or Vertical Printing Along the Wire or Simultaneous End Printing
Hot Stamp Foil	Bulk Foil in 100' & 600' Rolls See Foil Data Sheets for Complete Selection and Specifications
Power Requirement	110V Standard
Air Requirement	100 PSI / 5 CFM
Controls	<ul style="list-style-type: none"> On/Off Switch with Power on Indicator Test Mark and Test Cycle Functions Electronic Dwell Timer Solid-State Digital Temperature Controller with Actual and Set Point Read Out Air Pressure Regulator
Machine Supplied With	<ul style="list-style-type: none"> Heavy Duty Grounded Power Cord Generic Interconnect Kit for Various Wire Processors Air Pressure Regulator
Required Accessories	Typewheels, Wire-Holding Fixtures and Foil
Recommended Accessories	Extra Mandrel for Additional Typewheel Sets
Dimensions	Height: 14" (35.5 cm); Width: 7" (17.7 cm); Depth: 15" (38.1 cm)
Weight	Net: 52 lbs; Shipping: 55 lbs

Pricing and specifications are subject to change.

RIBBON

Diagram manufactures three industrial hot stamp ribbon formulations for the wire harness industry:

- Smudge-resistant heat transfer markings
- Black and white options available in all formulations
- No Fault Series specifically formulated to mark on PVC and cross-linked polyethylene (XLPE)
- K-520 Series designed to mark on slick surfaces

Contact our Ribbon Specialist for exclusive ribbon pricing offers. Call **1.800.722.1125** or visit **Diagram.com** to chat.




Diagram Marking & Coding

1 Research Park Drive
St. Charles, MO 63304-5685

+1 800 722 1125 | Diagram.com

An ITW Company

©2018 Diagram®